Hydrology Report For Lane Ranch Towne Center City of Lancaster, California

Hunsaker Project No: 0055-003-001 Prepared: 9/10/2008

Christopher Joseph & Associates 30851 Agoura Road, #210 Agoura, California 91301

Prepared by:

Hunsaker & Associates, Los Angeles, Inc. 26074 Avenue Hall Suite 22 Valencia CA 91355

Telephone: (661) 294-2211 Fax: (661) 294-9890

Under the direction of:

TABLE OF CONTENTS

- 1. INTRODUCTION
 - 1.1 Report Summary
 - 1.2 Project Description
- 2. METHODOLOGY
- 3. CONCLUSIONS & RECOMMENDATIONS
- 4. REFERENCES
- 5. APPENDICES
 - A: Time of Concentration Calculations Pre-Development Condition
 - 2-year
 - 10-year
 - 25-year
 - 50-year
 - B: Time of Concentration Calculations Post-Development Condition
 - 2-year
 - 10-year
 - 25-year
 - 50-year
 - C. Water Quality Calculations
 - SUSMP Calculation for onsite subareas
 - D. City Detention Letter to Lane Ranch LLC
 - E. Lane Ranch Hydrology Map
 - F. Approved Offsite Hydrology Map Tract 53229

1. INTRODUCTION

1.1 Project Description

The proposed Lane Ranch project is located in the southwesterly corner (Quartz Hill) of the City of Lancaster.. The proposed project consists of a 407,000 square foot commercial development located on approximately 38 acres at the southeast corner of 60th Street West and Avenue L.

The site is currently undeveloped and adjacent (east of) to the Quartz Hill High School. Immediately north and west of the site, future residential and commercial projects are currently under development. South of the site, a mixture of developed and undeveloped parcels currently exist within the limits of the Cities of Lancaster and Palmdale.

1.2 Report Summary

This report summarizes the hydrologic analysis for the proposed expansion of the Lane Ranch Towne Center. The pre and post-development onsite 50-Year, 24-Hour, and 25-Year, 24-Hour Peak Flows, and debris generation were calculated for the project. Offsite runoff rates and drainage systems are based upon The City of Lancaster Master Plan of Drainage dated January 2005, and the approved Hydrology for Tract 53229 (Prepared by CCL Engineering). Additional discussions were held with Mr. Carlyle S. Workman of the City of Lancaster

The methodology and assumptions used for this analysis is described in the following section.. Lastly, a conclusion of the results in included, with recommendations and a brief contrast of the existing condition versus the proposed design.

2. METHODOLOGY

A preliminary engineering analysis was performed to understand the existing hydrology and drainage of the site and its contributing tributary watersheds. Research was done at the City of Lancaster to obtain information on the surrounding site conditions. A field reconnaissance of the project site helped to further understand the existing hydrology of the site.

As previously stated, all offsite hydrology analysis is based upon the City's Master Plan of Drainage and the Approved Hydrology for Tract 53229. The onsite hydrology was calculated per the methods outlined in the 2006 Los Angeles County DPW Hydrology Manual. Analysis of the debris production was based on the Debris Production Rate Curves obtained from the LACDPW Sedimentation Manual, dated June 1993.

The Rational Method Time of Concentration methodology was applied to determine the individual sub-area's time of concentrations. Calculations were done with the LACDPW Tc Calculator.

Offsite flows from the areas south east of the site are routed in an existing storm drain located in 57th Street West. The existing storm drain extends northerly past Avenue L and then westerly to an existing detention basin. The detention basin is located at the northwest corner of Avenue L and 57th Street West. The existing drain then continues northerly in 57th Street West, then westerly in Avenue K-12 to the northeast corner of The Commons site, then northerly in 60th Street West.

Runoff from the site is assumed to be collected at the north westerly corner of the site and outletted into the existing detention basin.

The City of Lancaster design standards require that the site release no more than 85% of the pre-development peak 50-year runoff rate. All flow in excess of that amount must be detained. Lane Ranch will be required to contribute (see attached letter in Appendix) to the construction cost of the existing detention basin, which will serve as the mitigation for their onsite detention requirements. Any additional detention (if required) must be provided for in the site design or offsite improvements.

The City of Lancaster, while not a co-permittee with Los Angeles County for NPDES purposes, still requires treatment of the "First Flush" runoff. Water Quality (first flush) calculations are based upon the SUSMP calculations in the LACDPW SUSMP Manual for the 0.75 inch storm.

3. **CONCLUSIONS & RECOMMENDATIONS**

The proposed Lane Ranch Towne Center expansion would result in an overall increase in runoff from the site, with an overall decrease in debris. A summary of runoff rates follows in Table 3.1. The calculations can be found in the Appendix.

Table 3.1 Onsite Runoff Summary

Storm Event	Pre- development Runoff (cfs)	85 % Pre- development Runoff (cfs)	Post- development Runoff (cfs)	Peak Detention Rate (cfs)
2-year	3.1 cfs		13.7 cfs	
10-year	5.8 cfs	n/a	23.3 cfs	n/a
25-year	7.3 cfs	n/a	28.7 cfs	n/a
50-year	8.5 cfs	7.2 cfs	33.1cfs	Not required

The site will be required to construct the proposed 60 inch storm drain along the site in 60th Street West, and approximately 1300 feet westerly in Avenue L. At the terminus, the drain will connect into a proposed storm drain, or outlet through an energy dissipating structure.

Onsite water quality treatment can be performed by a number of methods, with the approval of the City of Lancaster Engineering Department, including water quality basins, bio-swales, bio-retention, continuous deflection systems, catch basin inserts, or other proprietary solutions. The peak design flow rate and volume is as follows:

Peak Mitigation Flow Rate: Opm =6.1 cfs Mitigation Volume: $Vm = 85.806 \text{ ft}^3$

4. <u>REFERENCES</u>

Los Angeles County Department of Public Works Hydrology Manual, January 2006

Los Angeles County Department of Public Works Sedimentation Manual, June 1993

Hydrology Study Tract No. 53229, Approved October 7, 2005

5. APPENDICES

Time of Concentration Calculations Pre-Development Condition A:

- 2-year10-year25-year50-year

(-d	<u>-</u>			
ioe) emilo	0.6	1 07	. 5	1.51
Irned flo. V	3.07	5.79	7.28	8.51
Pactor Bu	0.34	0.34	0.34	0.34
low rate (To Equatio Fire Factor Burned flow Vo	1.88 Tc=(10)^-0	3.33 Tc=(10)^-0	4.1 Tc=(10)^-0	4.73 Tc=(10)^-0
Ħ		0.12	0.12	0.12
S	0.1	0.1	0.1	0.1
culat Intensity (ir Cu	0.39	69.0	0.85	0.98
calculat Inte	30	30	30	30
ıyet (in. Tc⊷	1.5	2.7	3.3	3.8
Slope (ft/ft) Isohyet (in. Tc	0.008	0.008	0.008	0.008
ngth (ff)	1768	1768	1768	•
Type Le	134	134	134	134
requency Soi	2	10	25	20
ш.	0.02	0.02	0.02	0.02
Area (acre: %imp	40.2	40.2	40.2	40.2
Subarea	Ш	ш	ш	ш
Project	프	<u>ب</u>	LR	귀

Time of Concentration Calculations Post-Development Condition B:

- 2-year
 10-year
 25-year
 50-year

Cd Flow rate (Tc Equation 0.1 0.84 13.17 Tc=(10)^\cdot 0.05 0.1 0.84 23.3 Tc=(10)^\cdot 0.05 0.1 0.84 28.7 Tc=(10)^\cdot 0.05 0.1 0.84 33.09 Tc=(10)^\cdot 0.05 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84	Cd 0.1 0.84 0.1 0.84 0.1 0.84 0.1 0.84 0.1	Frequency Soil Type Length (tf) Slope (tf/ft) Isohyet (in. To-calculal Intensity (ir. Cu.) Cd. 2 134 2592 0.006 1.5 30 0.39 0.1 0.84 10 134 2592 0.006 2.7 30 0.69 0.1 0.84 25 134 2592 0.006 3.3 30 0.85 0.1 0.84 50 134 2592 0.006 3.8 30 0.98 0.1 0.84	Frequency Soil Type Length (ff) Slope (f/ff) Isohyet (in. To-calculal Intensity (ir. Cu. Cd. 2 134 2592 0.006 1.5 30 0.39 0.1 0.84 10 134 2592 0.006 2.7 30 0.69 0.1 0.84 25 134 2592 0.006 3.3 30 0.85 0.1 0.84 50 134 2592 0.006 3.8 30 0.98 0.1 0.84	Frequency Soil Type Length (ff) Slope (f/ff) Isohyet (in. To-calculal Intensity (ir. Cu. Cd. 2 134 2592 0.006 1.5 30 0.39 0.1 0.84 10 134 2592 0.006 2.7 30 0.69 0.1 0.84 25 134 2592 0.006 3.3 30 0.85 0.1 0.84 50 134 2592 0.006 3.8 30 0.98 0.1 0.84	Frequency Soil Type Length (tf) Slope (tf/ft) Isohyet (in. To-calculal Intensity (ir. Cu.) Cd. 2 134 2592 0.006 1.5 30 0.39 0.1 0.84 10 134 2592 0.006 2.7 30 0.69 0.1 0.84 25 134 2592 0.006 3.3 30 0.85 0.1 0.84 50 134 2592 0.006 3.8 30 0.98 0.1 0.84
	0.00.0	0.00.0	0.00.0	0.00.0	0.00.0	0.00.0	0.00.0	Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 0.1 10 134 2592 0.006 2.7 30 0.69 0.1 25 134 2592 0.006 3.3 30 0.85 0.1 50 134 2592 0.006 3.3 30 0.85 0.1 25 134 2592 0.006 3.8 30 0.98 0.1	Frequency Soil Type Length (ff) Slope (ff/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 0.1 10 134 2592 0.006 2.7 30 0.69 0.1 25 134 2592 0.006 3.3 30 0.85 0.1 50 134 2592 0.006 3.8 30 0.98 0.1	Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 0.1 10 134 2592 0.006 2.7 30 0.69 0.1 25 134 2592 0.006 3.3 30 0.85 0.1 50 134 2592 0.006 3.3 30 0.85 0.1 25 134 2592 0.006 3.8 30 0.98 0.1	Area (acre %imp Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu. 40.2 0.92 134 2592 0.006 1.5 30 0.39 0.1 40.2 0.92 10 134 2592 0.006 2.7 30 0.69 0.1 40.2 0.92 25 134 2592 0.006 3.3 30 0.85 0.1 40.2 0.92 50 134 2592 0.006 3.8 30 0.98 0.1
								Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 10 134 2592 0.006 2.7 30 0.69 25 134 2592 0.006 3.3 30 0.85 50 134 2592 0.006 3.8 30 0.98	Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 0.39 10 134 2592 0.006 2.7 30 0.69 25 134 2592 0.006 3.3 30 0.85 50 134 2592 0.006 3.8 30 0.98	Frequency Soil Type Length (ft) Slope (ft/ft) Isohyet (in. To-calculal Intensity (ir. Cu 2592 0.006 1.5 30 0.39 10 134 2592 0.006 2.7 30 0.69 25 134 2592 0.006 3.3 30 0.85 50 134 2592 0.006 3.8 30 0.98	Area (acre-%imp Frequency Soil Type Length (ft) Slope (ft/ft) lsohyet (in. To-calculal Intensity (ir. Cu. 40.2 0.92 2 134 2592 0.006 1.5 30 0.39 40.2 0.92 10 134 2592 0.006 2.7 30 0.69 40.2 0.92 25 134 2592 0.006 3.3 30 0.85 40.2 0.92 50 134 2592 0.006 3.8 30 0.98

- C. Water Quality Calculations
 - SUSMP Calculations

SUSUMP Calculations - LA county manual for standard Urban Storm Water mitigation plan

From Appendix A - Volume and Flow Rate Calculations Enter Ix from Table 1 - Appendix A based on assumed Tc

Cu From Runoff Coefficient Curve - Hydrology Manual Appendix C

LR

IMP% Length Slope **Total Area** lх 0.193 0.1 0.92 480 0.008 37.7

34.684 3.016

Formula $Cd = (0.9 \times IMP.) + [(1.0-IMP.)\times Cu]$

0.836

Cd x lx 0.161348

Tc Formula 10^-.507x(Cdxlx)^-.519 x length^0.483 x slope^-.135

30.35939

Formula Cd x lx x Atotal x 1.008333 Qpm

6.133508

Formula (2722.5*[(Ai)(0.9)+(Ap+Au)(Cu)]

Vm

85805.58

D. City Detention Letter to Lane Ranch LLC

805-723-6000

July 17, 1998

Mr. George Lane 44909 N. 10th Street West Lancaster, California 93534

Re: Detention Basin Construction at Avenue L and 57th Street West

Dear Mr. Lane:



Frank C. Roberts Mayor

Rev. Henry W. Hearts Vice Mayor

Michelle kilemaa Cornel Member

> नीक उन्होंक Council Member

Andrew D. Visokev Council Member

James C. Giller City Manager

As we discussed in our recent meeting, Stratham is proposing to construct a basin on the 5 acre parcel on the north side of Avenue L at approximately 57th Street West. In order to proceed, the one-third interest the Lanes have in this property needs to be granted to the City of Lancaster.

The basin, as currently designed, has a capacity of 20.6 acre-feet and will cost approximately \$70,000 to construct. Stratham will build the basin and install a chain link fence around the perimeter.

At the time the Lane Ranch property is developed, the City would require that the basin be enclosed with a block wall and wrought iron fence combination. These improvements, along with the one-third interest in the property, will constitute the Lane's contribution to the basin project. The block wall improvements and directing the runoff to the basin will also satisfy the requirement of mitigating the developmental runoff for the Lane Ranch project.

The cost to construct the block wall and wrought from fence combination has been estimated at approximately \$50,000. The City of Lancaster will construct the street improvements along the Avenue L frontage when the property on the east or west is developed.

The City hereby requests that the Lanes grant their interest in the property to the City and give Stratham permission to begin dewatering the basin. Your prompt attention to this matter is greatly appreciated. Should you need any additional information regarding this request, please contact Mr. Cariyle S. Workman at (805) 723-6079.

Sincerely

Neil K. Hudson City Engineer

CSW:lt

E. Lane Ranch Hydrology Map

F. Approved Offsite Hydrology Map Tract 53229